

LAND ARK PRODUCT GUIDE

Product	Product Description - More info available online at www.landarknw.com .
Primer/Base Coat	30% Original Finish/70% Pure Citrus Solvent for faster absorption on extremely green or dense species, or in high production situations; 4/1; 3/1; 2/1 ratios are also available, or buy Pure Citrus Solvent for your own custom blend. This step is not necessary, only optional for problem wood or more even staining.
Original Finish (previously 'Interior Finish')	Standard liquid clear finish for timbers, logs, T&G, etc. Fill all checks with product to greatly reduce checking; apply wet-on-wet. Coverage approx. 350 sq.ft or 500 bd.ft./gallon. Can be left on wood for 12-24 hours for maximum penetration. Apply with pad, sponge, brush, cotton T-shirt. Buff off excess. Avoid application in direct sun - it will dry too fast. Best all around finish safe for outside too.
Concentrated Finishing Oil	Great for flooring or fine woodwork, especially for use on reclaimed or super absorbant species. For floors, power buff with terry cloth pad, or thick cotton towel under white pad, edges tucked under and held by buffing wheel. Can ship by air. Same coverage and application as the Interior or Exterior Finish. Good general purpose finish, especially for fine furniture. Excellent Earthen Floor Finish!
Liquid Wax End Sealer (previously 'Non-Staining End Sealer/Liquid Wax')	A vastly superior end seal; will not stain. Also use as a great buffing finish and polish on any fine woodwork, window trim, doors or floors. Coverage 800+ sq.ft./gallon. Use with a ScotchBrite Stripping pad to clean dirt, abrasions from floors, counters, timbers, logs. For floors apply thin coat w/lambswool applicator. Let dry until stiff. Power buff as w/Concentrated using terry/towel method.
Exterior Finish (now with Zinc Oxide)	Apply 3 wet-on-wet coats; repeat with 1-2 coats in 3-6 months; and again in one year. Thorough treatment during the first two years is important. For optimal results, especially on a log home, pre-treat with borate salt mixed with water at 1/2-2/3 recommended strength. Use only the powder type that mixes with water!! The glycol base products adversely affect adhesion of the finish. Contains nano Zinc Oxide which serves as both an inert/non-toxic UVA inhibitor and Mildewcide. Coverage approx. 350 sq.ft or 500 bd.ft./gallon.
Concentrated Aniline Dye- TransTint brand- Interior Use Only	Comes pre-mixed to full intensity in your chosen finish. Thin with more clear finish to achieve desired shade if full strength is too dark. Two coats is most desirable on bare wood. Top coat with clear finish after 3-8 hours. For interior use only. Apply with brisk even strokes using a sponge, lambswool staining block or pad, or if using the Original or Exterior Finish, a pump up airless sprayer. Do not apply heavy and back brush unless you know how to use this technique; rather apply second coat for darker color. Color charts available online at www.landarknw.com or by mail or email. 4oz. color samples are available \$6/ea. or \$25 for pack of 5.
Concentrated Pigmented Mixol brand Oxide Stain - Interior or Exterior use	Comes pre-mixed to full intensity in your chosen finish. Thin with more clear finish to achieve desired shade if full strength is too dark. Two coats is most desirable on bare wood. Top coat with clear finish after 3-8 hours. For exterior use primarily, but can also be used indoors. Apply like you would the Aniline Dye above. Color charts available online at www.landarknw.com . 4oz. color samples are available \$6/ea. or \$25 for pack of 5.
Pure Tung Oil	100% pure with no additives. This is the highest quality tung oil available, drying harder and forming a more durable finish than linseed oil alone. Tung oil has a long successful history of use on a variety of surfaces. Mixed with Pure Citrus Solvent, Tung Oil makes a great natural floor finish. Our Tung Oil is dryer-free and slightly heat-treated (polymerized).
Pure Special Aged Linseed Oil	Purified and refined by natural oxidation and blowing, linseed oil dries as clear or clearer than tung oil, with none of the characteristic discoloration that is typical of hardware store varieties. No other finishing oil penetrates as deeply into wood. Our Linseed Oil is dryer-free and slightly heat-treated (polymerized).
Pure Citrus Solvent	High quality, food grade pure citrus oil, the purest form of citrus turpenes, extracted from cold-pressed orange peel oil as a byproduct of the juicing industry. It is also great for clean up around the job site or running through your sprayers after use with any oil or latex finishes or paints. Use like any degreaser or mineral spirits for a myriad of uses!
***Zinc Oxide Additive	A new additive we are offering to replace our previous UVA and Mildewcide found in our Exterior Finish, made of nano particles of Zinc Oxide which works as both a UVA inhibitor and fungistat or mildewcide. A non-chemical additive that delivers superior protection in the weather. Can also be used safely indoors.